

Standard Rooflights

# Williaam Cox Flatglass



## Product Overview

The Williaam Cox Flatglass range is a high quality, universal Glazed rooflight system.

The range is based on a highly insulated Double Glazed system structurally glazed to the cascade internal water management profiled system and fitted onto a Builders upstand to provide a low profiled sleek rooflight system.



## Application

- The system is suitable for Glazing into both Commercial and Domestic applications.
- The system can be installed to an angle as low as 10° or approach 75°.
- Various Sizes & glazing options available which provide excellent thermal efficiency.
- The system can be applied to any type of roof structure.



Williaam Cox offers an **extensive range of rooflight options.**  
Please speak to our sales department to discuss your requirements



Williaam Cox Ltd, Cloverhill Industrial Estate,  
Clondalkin, Dublin 22, Ireland

+353 (0)1 460 5400

admin@williaamcox.ie

www.williaamcox.com

# Standard Rooflights

## Williaam Cox Flatglass



## Specification

<b>Manufacturer</b>	Williaam Cox Ltd., Cloverhill Industrial Estate, Clondalkin, Dublin Ph: +353 (0)1 4605400, Email: admin@williaamcox.ie
<b>Product Ref</b>	Williaam Cox Flatglass Range
<b>Type</b>	Low Profile Structurally glazed Rooflight system
<b>Sizes</b>	Available on request
<b>Frame Finish</b>	Frames are available in Mill Finish, anodized, polyester powder coated, consult Williaam Cox Limited for further range and samples
<b>Glazing</b>	Standard Glazing Options: Outer glazing 6mm Outer Tough Soft Coat 18mm Airsparer 90% argon 8.4mm Inner Laminated,  Other glazing options available on request  Fire rating: Class B-s1, d0 to BS EN 13501-1:2002  Safety ACR [M] 001:2005. Class B Option available on request
<b>Other information:</b>	Maximum Wind Loading to BS 6399:1: 1.5kPa  Maximum Imposed Loading to BS 6399: 0.75kpa  Thermal Performance: u-values below 1.5W/m <sup>2</sup> K available  Part L compliant system.  Security fixed supplied as standard  Complies to current BS476 fire rating  Class B Non Fragile to ACR: M 2006