

Standard Rooflights

Williaam Cox Mark 1



Product Overview

The Williaam Cox Mark 1 range is a circular rooflight dome. It is available in double or triple glazed domes and can come with a polyester upstand or can suit a preformed builder's upstand.



Application

- The Williaam Cox Mark 1 range is our circular dome rooflight system.
- The range is based on an insulated 175mm GRP Upstand with single, double or triple skin polycarbonate glazing.
- Various glazing option available which provide excellent thermal efficiency.
- A quality, economical Part L compliant system.
- Exceptional waterproofing integrity.
- Complies to current BS476 fire rating.
- Class B Non-Fragile to ACR:M 2005.
- Suitable for any roofing application.



Williaam Cox offers an **extensive range of rooflight options.**

Please speak to our sales department to discuss your requirements



Williaam Cox Ltd, Cloverhill Industrial Estate,
Clondalkin, Dublin 22, Ireland

+353 (0)1 460 5400

admin@williamcox.ie

www.williamcox.com

Standard Rooflights

Williaam Cox Mark 1

Specification

Manufacturer	Williaam Cox Ltd., Cloverhill Industrial Estate, Clondalkin, Dublin Ph: +353 (0)1 4605400, Email: admin@williaamcox.ie	
Product Ref	Williaam Cox Mark 1	
Type	Circular Dome	
Sizes Rooflight size in mm (equals roof opening size):	<ul style="list-style-type: none"> • 600mm diameter • 750mm diameter • 900mm diameter • 1050mm diameter 	<ul style="list-style-type: none"> • 1200mm diameter • 1350mm diameter • 1500mm diameter • 1800mm diameter
Kerb	175 mm GRP kerb, designed to fit directly to the roof decking (by others)	
Glazing	Outer glazing to be 3mm Polycarbonate glazing with co-extruded UV protection in various options	
Tint options	Clear / Textured / Bronze / Opal	
Fire rating	Class B-s1, d0 to BS EN 13501-1:2002 Non-Fragile Class B to ACR[M]001:2005	

Typical Installation

