



GLASSLITE - ON 300mm UPSTAND

SCALE: NTS

GLASSLITE SPECIFICATIONS

- **Manufacturer:** Williaam Cox Ltd., Cloverhill Industrial Est., Clondalkin, Dublin
Ph: +353 (0)1 4605400
Email: admin@williaamcox.ie
- **Product Ref:** GLASSLITE
- **Type:** Flat Glass Rooflight
- **Opening options:** Manual/Electrical/ Solar Powered
- **Sizes:** 600mm x 600mm, 600mm x 900mm, 600mm x 1200mm, 600mm x 1500mm, 750mm x 750mm, 900mm x 900mm, 900mm x 1200mm, 900mm x 1500mm, 900mm x 1800mm, 1050mm x 1050mm, 1050mm x 1500mm, 1200mm x 1200mm, 1200mm x 1500mm, 1200mm x 1800mm, 1200mm x 2400mm, 1350mm x 1350mm, 1500mm x 1500mm, More sizes available.

- **Frame:** Thermally Broken Aluminium - RAL 7016 Anthracite Grey PPC Finish as Standard
- **Kerb Options:** Rigid Multiwall uPVC Kerb with 150mm Membrane termination point / Tall Kerb with 300mm Membrane termination point/ Direct Fix Kerb to suit builders upstand/ Dome Only for installation direct to builders upstand
- **Glazing:** Double Glazed glass unit. Centre Pane uValue 1.1W/m2K CWCT TN92 for Class 2 Roofs, ACR[M]001 Class B non Fragile

NO.	REVISION	DATE
CONTRACT.		
TITLE: Williaam Cox Glasslite - On 300mm Upstand		
ARCHITECT.		
MAIN CONTRACTOR.		
SCALE: 1:5	DWG. BY.	DWG. No.
DATE: Sept. 2020		WCL-BMG-300U



WILLIAM COX LTD.
Unit AF40 Cloverhill Industrial Estate, Clondalkin, Dublin 22
Tel: (01) 4605 400
Email: admin@williaamcox.ie
Web: www.williaamcox.com